

Appl. No. 10/698,143
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

In the Claims:

Claims 1-26 are canceled. New claims 27-29 are added.

1-26. (canceled)

27. (new) A method for fabricating a reflective type reflector plate of a reflective liquid crystal display, the method comprising the steps of:

preparing a glass substrate with thin film transistors built on a surface of the glass substrate;

forming transparent electrodes over the glass substrate after the thin film transistors are built on the glass substrate;

depositing a protection layer over the transparent electrodes;

patterning the transparent electrodes and the protection layer to form pixel patterns;

spin coating a photoresist layer over the protection layer using polymer resin material;

removing the photoresist layer over non-patterned areas; and depositing a reflective metal film over the photoresist layer retained on the glass substrate;

wherein after the protection layer is deposited over the transparent electrodes, the protection layer shields undesired reflection light during an exposure stage and reduces the exposure time.

Page 3 — RESPONSE (U.S. Patent Appln. S.N. 10/698,143)
[\\Files\files\Correspondence\August 2005\t1270rtoa083005.doc]

Appl. No. 10/698,143
Amdt. dated August 30, 2005
Reply to Office action of June 14, 2005

28. (new) The method as claimed in claim 27, wherein the protection layer is metal material.

29. (new) The method as claimed in claim 27, wherein the protection layer is non-metal material.